



## *POQ-30HJ/NP*

### *Long Arm Quilt & Skip Repair Machine*

Easy operation jump foot helps the operator follow the most intricate patterns on the largest and thickest panels.



*A great deal of value in every machine*

Specifications	POQ-30HJ/NP
Stitch type	single needle lockstitch
Max Speed-rpm	1250
Recommended speed-rpm	900
Needle type	135X17
Needle size	23
Needle height	3/4" (19 mm)
Presser foot height	1/2" (12.7 mm)
Clearance under arm	30" (76 cm)
Max. thickness capacity	4" (101 mm)
Motor type	servo needle positioner
Voltage	220/240VAC SINGLE PHASE (alternative voltages available)
Current (amps)	30 AMP(MAX)
Air pressure (psi)	80PSI
Air consumption (cfm)	6.00 SCFM @ 80PSI
Weight (gross)	490 lbs / 222 kg
Shipping Dimensions	45 X 65 X 37 / 114 X 165 X 94 cm

- 30" (760 cm) Clearance under the sewing machine arm allows repair anywhere on the mattress panel
- Includes electronic needle positioning servo motor
- Slim Presser foot design gives operator full vision in the sewing area
- Will repair from very thin panels and border up to very thick and dense quilt packages



Global Systems Group® (GSG) is a collection of the world's leading mattress machinery companies. These GSG machinery companies represent leading edge technology in computerized quilting machines and panel cutters; automated and conventional sewing machines; and mattress packaging equipment.



**GLOBAL SYSTEMS GROUP®**

A DIVISION OF *Leggett & Platt*  
INCORPORATED

13800 NW 4th Street  
Sunrise, FL 33325 USA

800-326-4742 954-846-0300 [www.GSGcompanies.com](http://www.GSGcompanies.com)